



GERSTEL


MPS Agitators

Specifications

Standard Agitator

- 6 positions
- 2 mL, 10 mL and 20 mL vials
- temperature range 35 ... 200 °C, in increments of 1 °C
- agitation speed 250 ... 750 rpm (\pm 15%)
- dimensions 180 x 115 x 185 mm (H x W x D)
- weight 2.2 kg

Agitator for 2 mL Vials

- 15 positions
- 2 mL vials
- temperature range 35 ... 200 °C, in increments of 1 °C
- agitation speed 250 ... 750 rpm (\pm 15%)
- dimensions 180 x 115 x 185 mm (H x W x D)
- weight 2.2 kg

Agitator for 40 mL Vials

- 4 positions
- 40 mL vials
- temperature range 35 ... 100 °C, in increments of 1 °C
- agitation speed 250 ... 750 rpm (\pm 15%)
- dimensions 245 x 115 x 230 mm (H x W x D)
- weight 3.4 kg

Incubator for 100 mL Vials

- 2 positions
- 100 mL vials
- temperature range 35 ... 180 °C, in increments of 1 °C
- dimensions 212 x 128 x 336 mm (H x W x D)
- weight 6.2 kg

Agitator Stirrer

- 6 positions
- 20 mL vials
- temperature range 35 ... 120 °C, in increments of 1 °C
- operation in agitation or stirring mode selectable
- agitation speed 250 ... 750 rpm (\pm 15%)
- stirring speed 500 ... 1500 rpm (\pm 15%)
- dimensions 180 x 115 x 185 mm (H x W x D)
- weight 2.2 kg

Cooled Agitator

- 6 positions
- 2 mL, 10 mL and 20 mL vials
- temperature range 10 ... 200 °C, in increments of 1 °C
- with peltier cooling UPC
- controlled by controller AUX 163 or C200
- dimensions 180 x 115 x 185 mm (H x W x D)
- weight 2.2 kg

Custom solutions for special performance requirements available on request

GERSTEL GmbH & Co. KG, Germany
gerstel@gerstel.de • www.gerstel.de
+49 208-7 65 03-0

GERSTEL AG, Switzerland
swiss@ch.gerstel.com • www.gerstel.de
+41 41-9 21 97 23

GERSTEL Inc., USA
sales@gerstel.us.com • www.gerstel.us.com
+1 410-247 5885

GERSTEL Brasil
gerstel@gerstel.com • www.gerstel.com.br
+55 11-5665 8931

GERSTEL K.K., Japan
info@gerstel.co.jp • www.gerstel.co.jp
+81 3 5731 5321

GERSTEL LLP, Singapore
sea@gerstel.com • www.gerstel.com
+65 6779 0933